

64292 XIR 150W 22.8V 40/CS 1/SKU



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54322
Product Name	64292 XIR 150W 22.8V 40/CS 1/SKU
Family Brand Name	XIR

Electrical data

Nominal Wattage	150 W
Nominal Voltage	22.8 V

Light technical data



Luminous Flux	6000 lm
Color Temperature	3250 K
Color Rendering Index	100
Average Rated Life	600 h

Physical attributes

Base	G6.35
Diameter d (in)	0.551 in
Diameter d (mm)	14.00 mm

Additional product data

Lamp Type	SINGLE END
-----------	------------



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54322	4008321330598	Folding box (SKU)	1	1 in x 0.9 in x 2.8 in	
54322	4008321330604	Shipping box (Case)	40	5.7 in x 4.2 in x 4.8 in	0.8 lb

Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
----------------	---------	-----------	----------	------------------------------	--------------

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.