

## 20W 12V PAR36 CAP 12/CS 1/SKU



### Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

### Areas of application

- Microscopy
- Laboratory & Analysis
- UV curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

# Product datasheet

## Technical data

### General product information

|                |                               |
|----------------|-------------------------------|
| Product Number | 55052                         |
| Product Name   | 20W 12V PAR36 CAP 12/CS 1/SKU |
| Application    | Landscaping                   |
| Product Remark | - WFL=Wide Flood              |

### Electrical data

|                 |      |
|-----------------|------|
| Nominal Wattage | 20 W |
| Nominal Voltage | 12 V |

### Light technical data

|                             |        |
|-----------------------------|--------|
| Beam Angle (degree)         | 25     |
| Centerbeam Candlepower (cp) | 550    |
| Color Rendering Index       | 100    |
| Average Rated Life          | 4000 h |

### Physical attributes

|                             |                    |
|-----------------------------|--------------------|
| Base                        | SCREW TERMINAL G53 |
| Bulb Shape                  | PAR36              |
| Maximum Overall Length (in) | 2.75 in            |
| Maximum Overall Length (mm) | 69.850 mm          |
| Length l (in)               | 2.75 in            |
| Length l (mm)               | 69.850 mm          |
| Diameter d (in)             | 4.500 in           |
| Diameter d (mm)             | 114.30 mm          |
| Filament                    | C-8                |

### Additional product data

|                    |       |
|--------------------|-------|
| Operating Position | Any   |
| Lamp Type          | PAR36 |

## Packaging Information

| Product number | EAN/UPC       | Packaging           | Quantity | Outside dimensions l x w x h | Gross weight |
|----------------|---------------|---------------------|----------|------------------------------|--------------|
| 55052          | 4008321470737 | Folding box (SKU)   | 1        | 3.5 in x 3.5 in x 4.1 in     | 0.6 lb       |
| 55052          | 4008321470744 | Shipping box (Case) | 12       | 14.7 in x 11.1 in x 4.9 in   | 7.4 lb       |

## Product datasheet

| Product number | EAN/UPC | Packaging | Quantity | Outside dimensions L x w x h | Gross weight |
|----------------|---------|-----------|----------|------------------------------|--------------|
|----------------|---------|-----------|----------|------------------------------|--------------|

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.