

## HMI DIGITAL 9000W 1/CS 1/SKU



### Product features and benefits

- Reduced flicker when used with high-speed electronic ballasts (up to 1000 Hz and higher)
- Suited for both analog and digital film productions
- High intensity light providing true color performance with a CRI>90
- Capable of hot restrike ignition
- High color stability with average changes in color temperature during lamp life only 1°K/hr
- High energy efficiency providing up to 100 LPW
- Enhanced safety with UV-Stop (UVS) feature on all DIGITAL types

### Areas of application

- Studio, TV and film
- Professional Photography
- Solar Simulation

## Product datasheet

---

### Technical data

#### General product information

Product Number	59941
Product Name	HMI DIGITAL 9000W 1/CS 1/SKU
Family Brand Name	HMI DIGITAL

#### Electrical data

Nominal Wattage	9000 W
Nominal Voltage	160 V

#### Light technical data

Luminous Flux	875000 lm
Color Temperature	6000 K
Color Rendering Index	90
Average Rated Life	400 h

#### Physical attributes

Base	GX38
Bulb Shape	T75

#### Additional product data

Lamp Type	SINGLE-END
-----------	------------

---

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
59941	4062172001908	Shipping box (Case)	1	28.1 in x 9.4 in x 9.4 in	4.9 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.