

FLK 575W 115V 12/CS 1/SKU



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54589
Product Name	FLK 575W 115V 12/CS 1/SKU
General Description	575 watt, tungsten halogen, medium to high voltage, single-ended
Application	Stage & Studio

Electrical data

Nominal Wattage	575 W
Nominal Voltage	115 V
Type of Current	AC

Light technical data

Luminous Flux	16500 lm
Light Center Length - LCL (in)	2.325 in
Light Center Length - LCL (mm)	59.055 mm
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	300 h

Physical attributes

Base	G9.5 Medium Bipin
Bulb Shape	T6
Maximum Overall Length (in)	3.976 in
Maximum Overall Length (mm)	101 mm
Length l (in)	3.939 in
Length l (mm)	101 mm
Length l max. (in)	3.939 in
Length l max. (mm)	101 mm
Diameter d (in)	0.625 in
Diameter d (mm)	15.88 mm
Distance a (in)	2.325 in
Distance a (mm)	59.055 mm
Filament	CC-8
Filament Dimensions Length (in)	0.6250 in
Filament Dimensions Length (mm)	15.88 mm
Filament Dimensions Width (in)	0.425 in

Product datasheet

Filament Dimensions Width (mm)	10.795 mm
--------------------------------	-----------

Additional product data

Operating Position	Any
Lamp Type	SINGLE END

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
54589	4062172146739	Folding box (SKU)	1	1.6 in x 1.6 in x 5.1 in	0.2 lb
54589	4062172146746	Shipping box (Case)	12	7 in x 5.4 in x 6 in	1.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.