

---

## HPL 750W 115V/X 12/CS 1/SKU



---

### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

---

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

# Product datasheet

## Technical data

### General product information

Product Number	54611
Product Name	HPL 750W 115V/X 12/CS 1/SKU
Family Brand Name	HPL
Application	Stage & Studio

### Electrical data

Nominal Wattage	750 W
Nominal Voltage	115 V
Type of Current	AC

### Light technical data

Luminous Flux	16400 lm
Light Center Length - LCL (in)	2.352 in
Light Center Length - LCL (mm)	60.3 mm
Color Temperature	3050 K
Color Rendering Index	100
Average Rated Life	1500 h

### Physical attributes

Base	G9.5 W/HSINK
Bulb Shape	T19
Maximum Overall Length (in)	4.1 in
Maximum Overall Length (mm)	104 mm
Length l (in)	4.1 in
Length l (mm)	104 mm
Length l max. (in)	4.1 in
Length l max. (mm)	104 mm
Diameter d (in)	0.748 in
Diameter d (mm)	19.00 mm
Distance a (in)	2.352 in
Distance a (mm)	60.3 mm
Filament	4-C8

### Additional product data

Operating Position	Any
--------------------	-----

# Product datasheet

## Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54611	4052899347922	Folding box (SKU)	1	1.6 in x 1.6 in x 5.1 in	0.2 lb
54611	4052899347939	Shipping box (Case)	12	7 in x 5.4 in x 6 in	1.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Disclaimer

OSRAM does not accept liability for errors, changes and omissions.