

HPL 575W 115V/X 12/CS 1/SKU



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54807	
Product Name	HPL 575W 115V/X 12/CS 1/SKU	
Family Brand Name	HPL	
Application	Stage & Studio	

Electrical data

Nominal Wattage	575 W
Nominal Voltage	115 V
Type of Current	AC

Light technical data

Luminous Flux	12360 lm
Light Center Length - LCL (in)	2.352 in
Light Center Length - LCL (mm)	60.3 mm
Color Temperature	3065 K
Color Rendering Index	100
Average Rated Life	2000 h

Physical attributes

Base	G9.5 W/HSINK	
Bulb Shape	T19	
Maximum Overall Length (in)	4.1 in	
Maximum Overall Length (mm)	104 mm	
Length l (in)	4.1 in	
Length I (mm)	104 mm	
Length I max. (in)	4.1 in	
Length I max. (mm)	104 mm	
Diameter d (in)	0.741 in	
Diameter d (mm)	19.00 mm	
Distance a (in)	2.352 in	
Distance a (mm)	60.3 mm	
Filament	4-C8	

Additional product data

Product datasheet

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54807	4062172147316	Folding box (SKU)	1	1.6 in x 1.6 in x 5.1 in	0.2 lb
54807	4062172147323	Shipping box (Case)	12	7 in x 5.4 in x 6 in	1.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.