

## FVL 200W 120V 24/CS 1/SKU



### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

# Product datasheet

## Technical data

### General product information

Product Number	54459
Product Name	FVL 200W 120V 24/CS 1/SKU
General Description	200 watt, tungsten halogen, medium to high voltage, single-ended
Application	Stage & Studio

### Electrical data

Nominal Wattage	200 W
Nominal Voltage	120 V
Type of Current	AC

### Light technical data

Luminous Flux	5200 lm
Light Center Length - LCL (in)	1.26 in
Light Center Length - LCL (mm)	32 mm
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	200 h

### Physical attributes

Base	GX5.3
Bulb Shape	T12
Maximum Overall Length (in)	2.125 in
Maximum Overall Length (mm)	54 mm
Length l (in)	2.125 in
Length l (mm)	54 mm
Diameter d (in)	0.500 in
Diameter d (mm)	12.70 mm
Distance a (in)	1.260 in
Distance a (mm)	32 mm
Filament	2 CC-8

### Additional product data

Operating Position	Any
Lamp Type	SINGLE END

## Product datasheet

---

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54459	4062172146296	Folding box (SKU)	1	1.3 in x 1.3 in x 3.5 in	0.1 lb
54459	4062172146302	Shipping box (Case)	24	8.3 in x 5.6 in x 4.5 in	1.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.