

BCM 20000W 208V 4/CS 1/SKU



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54713
Product Name	BCM 20000W 208V 4/CS 1/SKU
LIF Code	CP/99
Product Remark	- s (Operating Position) = Vertical, base down

Electrical data

Nominal Wattage	20000 W
Nominal Voltage	208 V

Light technical data

Luminous Flux	570000 lm
Luminous Efficacy (lm/W)	28.5 lm/W
Light Center Length - LCL (in)	13.806 in
Light Center Length - LCL (mm)	354 mm
Color Temperature	3200 K
Average Rated Life	400 h

Physical attributes

Base	G38
Bulb Shape	T31
Maximum Overall Length (in)	22.05 in
Maximum Overall Length (mm)	560 mm
Length l1 (in)	22.05 in
Length l1 (mm)	560 mm
Diameter d (in)	3.900 in
Diameter d (mm)	100.00 mm
Distance a (in)	13.806 in
Distance a (mm)	354 mm
Filament	C-13-8
Filament Dimensions Length (in)	2.6520 in
Filament Dimensions Length (mm)	68 mm
Filament Dimensions Width (in)	2.535 in
Filament Dimensions Width (mm)	65 mm

Additional product data

Operating Position	s45
--------------------	-----

Product datasheet

Cooling	any
Lamp Type	SINGLE END

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54713	10046135547130	Shipping box (Case)	1	21.9 in x 22.7 in x 28.9 in	26.5 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.