

## 64514 300W 120V 20/CS 1/SKU



### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

# Product datasheet

## Technical data

### General product information

Product Number	54766
Product Name	64514 300W 120V 20/CS 1/SKU
Application	Projector, Stage & Studio
LIF Code	CP/96

### Electrical data

Nominal Wattage	300 W
Nominal Voltage	120 V
Type of Current	AC

### Light technical data

Luminous Flux	8100 lm
Light Center Length - LCL (in)	1.053 in
Light Center Length - LCL (mm)	27 mm
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	75 h


### Physical attributes

Base	GX6.35 BIPIN
Bulb Shape	T6
Maximum Overall Length (in)	2.086 in
Maximum Overall Length (mm)	53 mm
Length l (in)	2.086 in
Length l (mm)	53 mm
Length l max. (in)	2.086 in
Length l max. (mm)	53 mm
Diameter d (in)	0.728 in
Diameter d (mm)	18.50 mm
Distance a (in)	1.053 in
Distance a (mm)	27 mm
Filament Dimensions Length (in)	0.4921 in
Filament Dimensions Length (mm)	12.5 mm
Filament Dimensions Width (in)	0.406 in
Filament Dimensions Width (mm)	10.3 mm

## Product datasheet

### Additional product data

Operating Position	s 90
--------------------	------



s 90

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54766	4008321746139	Folding box (SKU)	1	1.3 in x 1.5 in x 2.8 in	
54766	4008321746146	Shipping box (Case)	20	8.1 in x 5.6 in x 3 in	0.7 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.