

---

## ECT 500W 120V 24/CS 1/SKU



---

### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

---

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

## Product datasheet

---

### Technical data

#### General product information

Product Number	11520
Product Name	ECT 500W 120V 24/CS 1/SKU
Application	Photoflood

#### Electrical data

Nominal Wattage	500 W
Nominal Voltage	120 V
Type of Current	AC

#### Light technical data

Luminous Flux	13650 lm
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	60 h

#### Physical attributes

Base	MEDIUM
Bulb Shape	PS25
Filament	C-9

---

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
11520	4052899468023	Sleeve (SKU)	1	3 in x 3 in x 7.3 in	0.2 lb
11520	4052899431546	Shipping box (Case)	24	19.8 in x 13.4 in x 8.1 in	5 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.