

## 64788 CP/72 FTM 2000W 240V 12/CS 1/SKU



### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable to 0% with traditional amber shift

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

## Product datasheet

---

### Technical data

#### General product information

Product Number	54485
Product Name	64788 CP/72 FTM 2000W 240V 12/CS 1/SKU

#### Electrical data

Nominal Wattage	2000 W
Nominal Voltage	240 V
Type of Current	AC

#### Light technical data

Luminous Flux	52000 lm
Light Center Length - LCL (in)	2.76 in
Light Center Length - LCL (mm)	70 mm
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	400 h


#### Physical attributes

Base	GY16
Bulb Shape	T10
Length l (in)	5.71 in
Length l (mm)	145 mm
Diameter d (in)	1.339 in
Diameter d (mm)	34.00 mm
Distance a (in)	2.760 in
Distance a (mm)	70 mm

#### Additional product data

Operating Position	s90
Cooling	CONVECTION

Product datasheet



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54485	4008321632180	Folding box (SKU)	1	2.8 in x 2.8 in x 6.3 in	0.2 lb
54485	4008321984272	Shipping box (Case)	12	11.6 in x 8.7 in x 6.9 in	3.4 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.