

64805 CP/85 5000W 240V 6/CS 1/SKU



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable to 0% with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54553
Product Name	64805 CP/85 5000W 240V 6/CS 1/SKU
Application	Stage & Studio
LIF Code	CP/85
Product Remark	- s (Operating Position) = Vertical, base down

Electrical data

Nominal Wattage	5000 W
Nominal Voltage	240 V
Type of Current	AC

Light technical data

Luminous Flux	135000 lm
Light Center Length - LCL (in)	6.5 in
Light Center Length - LCL (mm)	165 mm
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	400 h


Physical attributes

Base	G38
Bulb Shape	T19
Length l (in)	11 in
Length l (mm)	279 mm
Diameter d (in)	2.362 in
Diameter d (mm)	60.00 mm
Distance a (in)	6.500 in
Distance a (mm)	165 mm
Filament	C13D

Additional product data

Operating Position	s45
Cooling	Convection

Product datasheet



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54553	4052899129573	Folding box (SKU)	1	13.3 in x 5.4 in x 5.6 in	1.1 lb
54553	4008321893611	Shipping box (Case)	6	16.6 in x 11.7 in x 13.7 in	8.9 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.