

93728 HPL 575W240V/X 12/CS 1/SKU



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable to 0% with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54703
Product Name	93728 HPL 575W240V/X 12/CS 1/SKU
Family Brand Name	HPL
Application	Stage & Studio

Electrical data

Nominal Wattage	575 W
Nominal Voltage	240 V
Type of Current	AC

Light technical data

Luminous Flux	11780 lm
Light Center Length - LCL (in)	2.352 in
Light Center Length - LCL (mm)	60.3 mm
Color Temperature	3050 K
Color Rendering Index	100
Average Rated Life	1500 h

Physical attributes

Base	G9.5 W/HSINK
Bulb Shape	T6
Maximum Overall Length (in)	4.1 in
Maximum Overall Length (mm)	104 mm
Length l (in)	4.1 in
Length l (mm)	104 mm
Length l max. (in)	4.1 in
Length l max. (mm)	104 mm
Diameter d (in)	0.748 in
Diameter d (mm)	19.00 mm
Distance a (in)	2.352 in
Distance a (mm)	60.3 mm
Filament	6-C8

Additional product data

Operating Position	Any
--------------------	-----

Product datasheet

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54703	4008321174444	Folding box (SKU)	1	1.6 in x 1.6 in x 5.1 in	0.2 lb
54703	4008321174451	Shipping box (Case)	12	6.9 in x 5.8 in x 5.7 in	2.1 lb
54703	4052899246867	Shipping box (Case)	12	7 in x 5.4 in x 6 in	2.6 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.