

64670 GCV 500W 230V 12/CS 1/SKU



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable to 0% with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54495
Product Name	64670 GCV 500W 230V 12/CS 1/SKU

Electrical data

Nominal Wattage	500 W
Nominal Voltage	230 V
Type of Current	AC

Light technical data

Luminous Flux	11000 lm
Light Center Length - LCL (in)	1.83 in
Light Center Length - LCL (mm)	46.5 mm
Color Temperature	3000 K
Color Rendering Index	100
Average Rated Life	300 h


Physical attributes

Base	GY9.5 BIPIN PREFOCUS
Bulb Shape	T6.5
Length l (in)	3.54 in
Length l (mm)	90 mm
Diameter d (in)	0.866 in
Diameter d (mm)	22.00 mm

Additional product data

Operating Position	s90
Cooling	CONVECTION
Lamp Type	SINGLE END

Product datasheet



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54495	4008321624017	Folding box (SKU)	1	1.6 in x 1.6 in x 5.1 in	0.1 lb
54495	4008321624024	Shipping box (Case)	12	7 in x 5.4 in x 5.4 in	1.5 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.