

---

## 64717 CP/89 FRL 650W 230V 12/CS 1/SKU



---

### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable to 0% with traditional amber shift

---

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

## Product datasheet

---

### Technical data

#### General product information

Product Number	54489
Product Name	64717 CP/89 FRL 650W 230V 12/CS 1/SKU
LIF Code	CP/89

#### Electrical data

Nominal Wattage	650 W
Nominal Voltage	230 V
Type of Current	AC

#### Light technical data

Luminous Flux	16250 lm
Light Center Length - LCL (in)	1.83 in
Light Center Length - LCL (mm)	46.5 mm
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	150 h


#### Physical attributes

Base	GY9.5
Bulb Shape	T6.5
Length l (in)	3.54 in
Length l (mm)	90 mm
Diameter d (in)	0.866 in
Diameter d (mm)	22.00 mm
Distance a (in)	1.830 in
Distance a (mm)	46.5 mm
Filament	C13D

#### Additional product data

Operating Position	s90
Cooling	CONVECTION
Lamp Type	SINGLE-END

## Product datasheet



### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54489	4008321624215	Folding box (SKU)	1	1.6 in x 1.6 in x 5.1 in	0.1 lb
54489	4008321624222	Shipping box (Case)	12	7 in x 5.4 in x 6 in	1.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.