

## 6.6A 48W MR16 64337A 48-15 20/CS 1/SKU



### Product features and benefits

- Low maintenance costs due to long lamp life
- Reliable and consistent light output enhances visibility over the life of the lamp
- FAA approved in conjunction with many OEM fixtures
- Durable construction provides resistance to the effects of vibration
- Broad product portfolio for runway, taxiway, and approach lighting
- IR radiation provides guidance in low visibility conditions
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free

### Areas of application

- Airfield lighting

## Product datasheet

### Technical data

#### General product information

Product Number	58891
Product Name	6.6A 48W MR16 64337A 48-15 20/CS 1/SKU
Application	Airfield/Airport
Product Remark	– Female contact is according to DIN 46247.

#### Electrical data

Nominal Wattage	48 W
Current (A)	6.6 A
Type of Current	AC

#### Light technical data

Luminous Intensity (cd)	23000 cd
Color Rendering Index	100
Average Rated Life	1500 h

#### Physical attributes

Base	LEADS W/MALE FLAT CONNECTORS
Bulb Shape	MR16
Maximum Overall Length (in)	1.772 in
Maximum Overall Length (mm)	45 mm
Diameter d (in)	1.984 in
Diameter d (mm)	50.40 mm

#### Additional product data

Operating Position	Any
Lamp Type	SINGLE ENDED

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
58891	4008321102737	Folding box (SKU)	1	1.9 in x 1.9 in x 2.4 in	0.1 lb
58891	4008321102744	Shipping box (Case)	20	10.1 in x 4.3 in x 5.2 in	1.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Product datasheet

---

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.