

---

## TP22HCE 165CM16GAUL1659 40/CS 10/SKU



---

### Product features and benefits

- Ceramic housings designed specifically for high temperature halogen and metal halide applications
- High quality contact materials for optimal mechanical and electrical properties
- UL recognized and CE certified

---

### Areas of application

- Halogen Fixtures
- Metal Halide Fixtures
- Halogen Instrumentation
- Halogen Equipment

## Product datasheet

### Technical data

#### General product information

Product Number	69017
Product Name	TP22HCE 165CM16GAUL1659 40/CS 10/SKU
CSA File No.	LR20904

#### Electrical data

Maximum Wattage (W)	1000 W
Maximum Voltage (V)	250 V

#### Physical attributes

Length (in)	0.75 in
Length (mm)	19 mm
Width (in)	0.85 in
Width (mm)	21.7 mm
Height (in)	0.43 in
Height (mm)	10.8 mm
Body Material	Ceramic Steatite
Contact Material	Silver Plated Nickel
Wire Type	UL 1659
Wire Gauge (AWG)	16 AWG
Wire Color(s)	Brown, Blue, Green
Lead Strip Length (in)	0.25 in
Lead Strip Length (mm)	6.35 mm

#### Additional product data

Lamp Base Reference	G9.5, Bi-Pin
Maximum Operating Temperature (°C)	250 C
Rohs Compliant	Yes
Underwriters Laboratories File No.	E31557

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69017	4052899016002	Shipping box (Case)	10	10.1 in x 7.4 in x 3.1 in	4 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Product datasheet

---

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.