OSRAM

LEDriving HL INTENSE NXT H4



Up to +400% more brightness 1)

More light¹⁾ allows to see farther and therefore react sooner. Obstacles and hazards can be recognized sooner on race tracks.Compared to minimum ECE R112



CANbus free

Prevents error messages in board computers during failure detection



Compact LED replacement for conventional H4 high and low beam lamps

Easy installation thanks to a wide range of suitable OSRAM accessories



5-year OSRAM guarantee

For precise conditions, please refer to www.osram.com/amguarantee



OSRAM's highest performing off-road LED retrofit lamp ever!

With up to +400% more brightness1) and integrated CANbus (for avoiding error messages on the dashboard2) the OSRAM LEDriving HL INTENSE NXT ensures a compact LED replacement of conventional H4 high and low beam lamps. These LED retrofit lamps are 12V compatible, come with an optimized beam pattern, color temperature of 6,000 K and thanks to the wide range of suitable OSRAM accessories the installation is easy. The top OSRAM thermal management technology with integrated active cooling – a high speed fan - provides maximized heat dissipation for more powerful performances. Premium OSRAM quality and LED technology grant up to 5 times more lifetime (compared to traditional halogen bulbs). The pair of lamps comes with a 5-year OSRAM guarantee3).

- 1) compared to minimum ECE R112
- 2) applicable to plenty of car models 3For precise guarantee conditions please refer to www.osram.com/am-guarantee.

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

	Product information			General Pro Information	=====================================		Data	
Product description	Application (Category and Product specific)		Product type (off- road vs. on-road)	Global order reference		Power input	Nominal voltage	
LEDriving HL INTENSE NXT ≜ H4	Mainly used for Low Beam, High Beam		Off-road ≙ H4			40.0 W/ 12.0 V 42.0 W		
				Photometric	Data		Physical Attributes & Dimensions	
Product description	Nominal wattage		Test voltage	100		Luminous flux tolerance	Diameter	
LEDriving HL INTENSE NXT ≜ H4	40.0 W/ 42.0 W		13.2 V	2500/3500 lm		±25 %	15.5 mm	
	Lifetime Data	Capabilities	1	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)				
Product description	Lifespan Tc	Technology	Primary a identifier		ticle Candidate list substance 1		Declaration no. in SCIP database	
LEDriving HL INTENSE NXT ≜ H4	2500 hr	LED	4062172	4062172408158		able	No declarable	

Product family datasheet

Download Data

File



User instruction

LEDriving HL INTENSE NXT H4 64193DWINN



User instruction

GPRS_Safety symbols instructions

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.





